

B2  
✓ supporting position, and a carrier detachably mounted on an upper portion of said cart for transporting a closed bag or sack, said carrier having a pair of elongated jaws, each of said jaws having a gripping surface for clamping said jaws to and releasing said jaws from an upper portion of [a] said closed bag or sack, a means for said clamping and releasing said jaws from said upper portion of said closed bag or sack, and a handle attached to said carrier.

---

20. (amended) The combination set forth in claim 5 wherein at least one of said jaws has a gripping surface for retaining and supporting said upper portion of said closed bag or sack.

B  
3 21. (amended) The combination set forth in claim 5 wherein said gripping surface of said jaw is comprised of a plurality of small outward extending portions for retaining and supporting said closed bag or sack.

22. (amended) The combination set forth in claim 5 further comprising a thin metal strip attached to at least one of said jaws, said metal strip having a plurality of outward extending tabs for forming a gripping surface to retain and support said closed bag or sack; a means for clamping said jaws to and releasing said jaws from said upper portion of said closed bag or sack; and a handle attached to said carrier.

---

B  
4 24. (amended) In combination, a cart having at least one pair of wheels for transporting said cart and a carrier mounted on said cart for supporting [a] an upper portion of a closed bag or a sack on said cart, said carrier having a pair of jaws for clamping said upper portion of said closed bag or sack to said carrier; and a means for said clamping and said releasing of said jaws from said upper portion of said closed bag or sack.

---